



## RISING STAR™ TECHNICAL DATA

### FACTS

<b>Factory Finish:</b>	1500 Polished	<b>Flare Potential:</b>	3 - 4 Inches
<b>Lane Condition:</b>	Medium – Light Oil	<b>Cover Stock:</b>	Ultimate Vision™ Hybrid Reactive
<b>Weight Block:</b>	Neutron™ Core	<b>Color:</b>	Black Solid/ Gold Pearl
<b>D-Scale:</b>	75 – 78	<b>Available Weights:</b>	10 - 16 Pounds
<b>SKU:</b>	BBMRIS		

### CORE DYNAMICS

<b>WEIGHT</b>	16 lb.	15 lb.	14 lb.	13 lb.	12 lb.	11 lb.	10 lb.
<b>RG VALUE</b>	<b>2.56</b>	<b>2.55</b>	<b>2.60</b>	<b>2.67</b>	<b>2.67</b>	<b>2.73</b>	<b>2.77</b>
<b>RG DIFFERENTIAL</b>	<b>.046</b>	<b>.042</b>	<b>.044</b>	<b>.017</b>	<b>.017</b>	<b>.012</b>	<b>.015</b>

### RESURFACING METHOD

Follow the steps below to take the ball back to “out of the box” condition.

- Items needed: 500-grit and 1000-grit Abralon Pads, Storm Step #2 Polish, a ball spinner, and water. All sanding should be done on four sides of the ball.
- Side one: Center of grip up, flip the ball 180 degrees for side two, turn 90 degrees for side three and flip another 180 degrees for side four.
  1. Using the 500-grit Abralon pad, sand the ball for 15 seconds on each side
  2. Using the 1000-grit Abralon pad, sand the ball for 8 seconds on each side
  3. Using the Storm Step #2, polish the ball on two sides for 15 seconds on each side
- To touch up the surface, skip step #1 and just use steps #2 and #3.

Roto Grip® suggests using step #2 and #3 from above, every 10-15 games and all 3 steps every 30-60 games. This will keep the surface of the ball more constant, resulting in increased longevity and a more consistent reaction.

